UL Product **iQ**™



VENF.EX15802 - Flexible Sprinkler Hose with Fittings

Flexible Sprinkler Hose with Fittings

See General Information for Flexible Sprinkler Hose with Fittings

NEWAGE FIRE PROTECTION INDUSTRIES PVT LTD

EX15802

Equivalent

4, Champaklal Udyong Bhavan, Sion E Mumbai, Maharashtra 400022 INDIA

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
NI25 UB-07 unbraided	175	225	1 X 1/2	2.3 (700)	2	4 (100)	16	Limited
NI25 UB-10 unbraided	175	225	1 X 1/2	3.3 (1000)	3	4 (100)	34	Limited
NI25 UB-12 unbraided	175	225	1 X 1/2	3.9 (1200)	3	4 (100)	35	Limited
NI25 UB-15 unbraided	175	225	1 X 1/2	4.9 (1500)	3	4 (100)	52	Limited
NI25 UB-18 unbraided	175	225	1 X 1/2	5.9 (1800)	3	4 (100)	84	Limited
NI25 UB-07 unbraided	175	225	1 X 3/4	2.3 (700)	2	4 (100)	22	Limited
NI25 UB-10 unbraided	175	225	1 X 3/4	3.3 (1000)	3	4 (100)	43	Limited
NI25 UB-12 unbraided	175	225	1 X 3/4	3.9 (1200)	3	4 (100)	50	Limited
NI25 UB-15 unbraided	175	225	1 X 3/4	4.9 (1500)	3	4 (100)	59	Limited
NI25 UB-18 unbraided	175	225	1 X 3/4	5.9 (1800)	3	4 (100)	86	Limited
NI27-SB-700 braided	200	150	1x1/2	2.3 (700)	2	5	33	Limited
NI27-SB-1000 braided	200	150	1x1/2	3.3 (1000)	3	5	65	Limited
NI27-SB-1200 braided	200	150	1x1/2	3.9 (1200)	3	5	67	Limited

		V = 1 11 . E / 1	OOOZ TICKII	ле эрппкіег г	103C WILLI I	90 02 1 10	duot iQ	
NI27-SB-1500 braided	200	150	1x1/2	4.9 (1500)	3	5	84	Limited
NI27-SB-1800 braided	200	150	1x1/2	5.9 (1800)	3	5	101	Limited
NI27-SB-700 braided	200	150	1x3/4	2.3 (700)	2	5	36	Limited
NI27-SB-1000 braided	200	150	1x3/4	3.3 (1000)	3	5	59	Limited
NI27-SB-1200 braided	200	150	1x3/4	3.9 (1200)	3	5	73	Limited
NI27-SB-1500 braided	200	150	1x3/4	4.9 (1500)	3	5	77	Limited
NI27-SB-1800 braided	200	150	1x3/4	5.9 (1800)	3	5	105	Limited
NFAP25-07 unbraided	200	150	1x1/2	2.3 (700)	2	5	33	Limited
NFAP25-10 unbraided	200	150	1x1/2	3.3 (1000)	3	5	65	Limited
NFAP25-12 unbraided	200	150	1x1/2	3.9 (1200)	3	5	67	Limited
NFAP25-15 unbraided	200	150	1x1/2	4.9 (1500)	3	5	84	Limited
NFAP25-18 unbraided	200	150	1x1/2	5.9 (1800)	3	5	101	Limited
NFAP25-07 unbraided	200	150	1x3/4	2.3 (700)	2	5	36	Limited
NFAP25-10 unbraided	200	150	1x3/4	3.3 (1000)	3	5	59	Limited
NFAP25-12 unbraided	200	150	1x3/4	3.9 (1200)	3	5	73	Limited
NFAP25-15 unbraided	200	150	1x3/4	4.9 (1500)	3	5	77	Limited
NFAP25-18 unbraided	200	150	1x3/4	5.9 (1800)	3	5	105	Limited
NI25 B-6 Braided	175	225	1x1/2	2.0 (610)	1	7.5	12	Limited
NI25 B-12 Braided	175	225	1x1/2	4.0 (1220)	3	7.5	29	Limited
NI25 B-15 Braided	175	225	1x1/2	5.0 (1525)	3	7.5	68	Limited
NI25 B-18 Braided	175	225	1x1/2	5.9 (1800)	3	7.5	94	Limited
NI25 B-6 Braided	175	225	1x3/4	2.0 (610)	1	7.5	21	Limited

NI25 B-12 Braided	175	225	1x3/4	4.0 (1220)	3	7.5	36	Limited
NI25 B-15 Braided	175	225	1x3/4	5.0 (1525)	3	7.5	73	Limited
NI25 B-18 Braided	175	225	1x3/4	5.9 (1800)	3	7.5	99	Limited

The braided flexible sprinkler hose with fittings, NI27-SB series are intended to be installed with the L-Bracket and S-Bracket in accordance with the manufacturer's installation instructions dated June 12, 2018.

The unbraided type flexible sprinkler hose with fittings, NI25 UB series are intended to be installed with the A-DFM middle and end bracket combination in accordance with the manufacturer's installation instructions or with the B-COT middle and B-EOT end bracket combination in accordance with the manufacturer's installation instructions dated 21th of December, 2018. The braided flexible sprinkler hose with fittings, NI27-SB series and the unbraided flexible sprinkler hose with fittings, NFAP25 Series are intended to be installed with the L-Bracket and S-Bracket in accordance with the manufacturer's installation instructions dated January 14, 2019. The braided type flexible sprinkler hose with fittings, NI25 B series are intended to be installed with the A-DFM middle and end bracket combination or the B-CON-B middle and B-EL-B end bracket combination in accordance with the manufacturer's installation instructions dated 19th of February, 2019.

Trademark and/or Tradename:



Last Updated on 2019-06-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"